

PropPaint Qld. ABN: 66 921 859 895  
Phone: 0418 928 377  
Fax: 07 5537 8746

Email: [admin@proppaintqld.com.au](mailto:admin@proppaintqld.com.au)  
Web: [www.proppaintqld.com.au](http://www.proppaintqld.com.au)



# VINYL ETCH PRIMER APPLICATION GUIDE

## Vinyl Etch Primer, Adhesion Promoter for Velox Plus

**This Etch Primer is a Two-part system; you must ensure you mix equal parts of Part A and Part B together.**

**1:1 mix**

### Applications for use

1. Remove existing paint coatings.
2. Clean surface with a Wax and Grease Remover or Polyurethane Thinner,
3. Ensure to wipe dry with a clean cloth (do not let solvent evaporate before wiping dry).
4. Sand Metal work with 80gt sandpaper.  
**ENSURE SANDED METAL IS OVERCOATED WITHIN 6 HRS OF SANDING.**
5. Mix equal parts of Vinyl Etch Primer base and catalyst together and apply 1 thin coat only.

After allowing to dry for 30 mins minimum, continue with Application of Metal Primer as per '*Velox Plus Application Guide*'

- Do not apply if temperature is below 10C or Humidity above 80%

**Please Note: Vinyl Etch Primer is translucent do not apply thick coats.**